

## SAFETY DATA SHEET

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name                      MONDIAL TYRE SHINE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses                      Polish.

1.3. Details of the supplier of the safety data sheet

Supplier                              MONDIAL UTILITIES  
    5 WALLY PLACE  
    LYNBROOK VIC  
    3975  
    03 8753 6500  
 Manufacturer                      [info@mondialutilities.com.au](mailto:info@mondialutilities.com.au)

1.4. Emergency telephone number

000

## SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Aerosol 1 - H222
Human health	Eye Irrit. 2 - H319
Environment	Not classified.

Classification (1999/45/EEC) F+;R12.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

2.2. Label elements

## TYRE SHINE

## Detergent Labelling:

5 - < 15%  
< 5%

Aliphatic hydrocarbons  
non-ionic surfactants  
anionic surfactants

Contains

Benzisothiazolinone, Methylisothiazolinone

Label In Accordance With (EC) No. 1272/2008



## Signal Word

Danger

## Hazard Statements

H222

Extremely flammable aerosol.

H319

Causes serious eye irritation.

## Precautionary Statements

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P210

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211

Do not spray on an open flame or other ignition source.

P251

Pressurized container: Do not pierce or burn, even after use.

P280

Wear eye and face protection.

P305+351+338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501

Dispose of contents/container in accordance with local regulations.

## Supplementary Precautionary Statements

P264

Wash contaminated skin thoroughly after handling.

## 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2. Mixtures

DIETHANOLAMINE		0.0001 - <0.1%
CAS-No.: 111-42-2	EC No.: 203-868-0	
Classification (EC 1272/2008)		Classification (67/548/EEC)
Acute Tox. 4 - H302		Xn;R22,R48/22
Skin Irrit. 2 - H315		Xi;R38,R41
Eye Dam. 1 - H318		
STOT RE 2 - H373		

## TYRE SHINE

DIETHYLENE GLYCOL		0.0001 - <0.1%
CAS-No.: 111-46-6	EC No.: 203-872-2	
Classification (EC 1272/2008) Acute Tox. 4 - H302	Classification (67/548/EEC) Xn;R22	
ISOTRIDECANOL, ETHOXYLATED (>5-20 EO)		1.0 - <3.0%
CAS-No.: 69011-36-5	EC No.: 931-138-8	
Classification (EC 1272/2008) Acute Tox. 4 - H302 Eye Dam. 1 - H318	Classification (67/548/EEC) Xn;R22. Xi;R41.	
PETROLEUM GASES, LIQUEFIED		10.0 - <20.0%
CAS-No.: 68476-85-7	EC No.: 270-704-2	
Classification (EC 1272/2008) Flam. Gas 1 - H220 Press. Gas - H280	Classification (67/548/EEC) F+;R12.	
SODIUM N-LAUROYLSARCOSINATE		0.5 - < 1.0%
CAS-No.: 137-16-6	EC No.: 205-281-5	
Classification (EC 1272/2008) Acute Tox. 2 - H330 Skin Irrit. 2 - H315 Eye Dam. 1 - H318	Classification (67/548/EEC) T;R23. Xi;R41,R38.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: FIRST AID MEASURES

## 4.1. Description of first aid measures

## General information

Get medical attention if any discomfort continues. Remove affected person from source of contamination. General first aid, rest, warmth and fresh air. NOTE! Effects may be delayed. Keep affected person under observation.

## Inhalation

Remove victim immediately from source of exposure. In case of inhalation of spray mist: Move person into fresh air and keep at rest. Move injured person into fresh air and keep person calm under observation. If necessary, seek hospital and bring these instructions. Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Immediately call an ambulance.

## Ingestion

Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions. Provide rest, warmth and fresh air. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs.

## TYRE SHINE

### Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Consult a physician for specific advice.

### Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Do not rub eye. Get medical attention promptly if symptoms occur after washing.

### 4.2. Most important symptoms and effects, both acute and delayed

#### General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure. NOTE! Effects may be delayed. Keep affected person under observation.

#### Inhalation

May cause an asthma-like shortness of breath. In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Drowsiness, dizziness, disorientation, vertigo. Vapours may cause drowsiness and dizziness. In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication. Due to the physical nature of this material it is unlikely that swallowing will occur.

#### Skin contact

Prolonged contact may cause redness, irritation and dry skin. May cause skin irritation/eczema.

#### Eye contact

Extreme irritation of eyes and mucous membranes, including burning and tearing. Vapour, spray or dust may cause chronic eye irritation or eye damage. May cause blurred vision and serious eye damage.

### 4.3. Indication of any immediate medical attention and special treatment needed

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Extinguishing media

Use: Foam, carbon dioxide or dry powder. Water spray. Use fire-extinguishing media appropriate for surrounding materials.

#### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

#### Hazardous combustion products

In case of fire, toxic gases (CO, CO<sub>2</sub>, NO<sub>x</sub>) may be formed. During fire, toxic gases (CO, CO<sub>2</sub>, NO<sub>x</sub>) are formed.

#### Unusual Fire & Explosion Hazards

Extremely flammable. Severe explosion hazard when vapours are exposed to flames. Risk of explosion if heated. Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back. Heat may cause the containers to explode. Aerosol cans may explode in a fire.

#### Specific hazards

Aerosol containers can explode when heated, due to excessive pressure build-up. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive air mixtures even at room temperature.

### 5.3. Advice for firefighters

## TYRE SHINE

### Special Fire Fighting Procedures

Be aware of risk of fire re-starting, and risk of explosion. Cool containers exposed to flames with water until well after the fire is out. Use water to keep fire exposed containers cool and disperse vapours.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours and aerosol spray. In case of spills, beware of slippery floors and surfaces.

### 6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground. The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

### 6.3. Methods and material for containment and cleaning up

For waste disposal, see section 13. If leakage cannot be stopped, evacuate area. Stop leak if possible without risk. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Remove sources of ignition. Collect with absorbent, non-combustible material into suitable containers.

### 6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Wear full protective clothing for prolonged exposure and/or high concentrations. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Do not use in confined spaces without adequate ventilation and/or respirator. Mechanical ventilation or local exhaust ventilation may be required. Observe occupational exposure limits and minimise the risk of inhalation of vapours and mist.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Keep upright. Protect against physical damage and/or friction. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Do not store for long periods or in large quantities. Store in a cool and well-ventilated place. Store in a dry place. Do not store near heat sources or expose to high temperatures.

Storage Class

Flammable liquid storage.

### 7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
DIETHANOLAMINE	OES	3 ppm	15 mg/m <sup>3</sup>			
DIETHYLENE GLYCOL	WEL	23 ppm	101 mg/m <sup>3</sup>			
PETROLEUM GASES, LIQUEFIED	WEL	1000 ppm	1750 mg/m <sup>3</sup>	1250 ppm	2180 mg/m <sup>3</sup>	Carc

## TYRE SHINE

WEL = Workplace Exposure Limit.

Carc = Capable of causing cancer and/or heritable genetic damage.

### 8.2. Exposure controls

#### Protective equipment



#### Engineering measures

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of spray.

Provide explosion proof ventilation for high concentrations.

#### Respiratory equipment

In case of inadequate ventilation use suitable respirator.

#### Hand protection

No specific hand protection noted, but gloves may still be advisable.

#### Eye protection

Wear approved, tight fitting safety glasses where splashing is probable.

#### Other Protection

Provide eyewash station. Wear appropriate clothing to prevent repeated or prolonged skin contact.

#### Hygiene measures

Wash contaminated clothing before reuse. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. DO NOT SMOKE IN WORK AREA! When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Milky.
Solubility	Insoluble in water
Initial boiling point and boiling range (°C)	Technically not feasible.
Melting point (°C)	Not determined.
Relative density	1.00 - 1.05
Vapour density (air=1)	Not determined.
Vapour pressure	Not determined.
Evaporation rate	Not determined.
pH-Value, Conc. Solution	8.0 - 10.0
Decomposition temperature (°C)	Not determined.

## TYRE SHINE

Odour Threshold, Lower

Not determined.

Odour Threshold, Upper

Not determined.

Flash point (°C)

Technically not feasible.

Auto Ignition Temperature (°C)

Not determined.

Flammability Limit - Lower(%)

Not determined.

Flammability Limit - Upper(%)

Not determined.

Partition Coefficient

(N-Octanol/Water)

Not determined.

Oxidising properties

Not available.

### 9.2. Other information

None.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

No specific reactivity hazards associated with this product. The product may form explosive vapours/air mixtures even at normal room temperatures.

### 10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

### 10.3. Possibility of hazardous reactions

Not relevant

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

### 10.5. Incompatible materials

Materials To Avoid

No incompatible groups noted.

### 10.6. Hazardous decomposition products

None under normal conditions.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Toxicological information

No information available.

#### Carcinogenicity:

Does not contain any substances known to be carcinogenic.

#### Reproductive Toxicity:

No evidence of reproductive toxicity in animal studies

## TYRE SHINE

### Target Organs

Central nervous system

Central nervous system depression including narcotic effects such as drowsiness, narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

### Target Organs

Skin

Morphological changes that are potentially reversible but provide clear evidence of marked organ dysfunction.

### Aspiration hazard:

Not relevant, due to the form of the product.

### General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

### Inhalation

Vapour from this chemical can be hazardous when inhaled. Vapours have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

### Ingestion

No harmful effects expected in amounts likely to be ingested by accident.

### Skin contact

Contains components which may penetrate the skin. Repeated exposure may cause skin dryness or cracking.

### Eye contact

Spray and vapour in the eyes may cause irritation and smarting.

### Health Warnings

This chemical can be hazardous when inhaled and/or touched. May cause severe internal injury. Vapour from this chemical can be hazardous when inhaled.

### Route of entry

Inhalation. Skin and/or eye contact.

### Target Organs

Central nervous system Eyes Skin

### Medical Symptoms

Skin irritation. Irritation of eyes and mucous membranes. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo.

### Medical Considerations

Skin disorders and allergies. Pre-existing eye problems.

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

#### 12.1. Toxicity

##### Acute Toxicity - Fish

Not available.

##### Acute Toxicity - Aquatic Invertebrates

Not available.



## TYRE SHINE

### 12.2. Persistence and degradability

#### Degradability

There are no data on the degradability of this product.

### 12.3. Bioaccumulative potential

#### Bioaccumulative potential

No data available on bioaccumulation.

#### Partition coefficient

Not determined.

### 12.4. Mobility in soil

#### Adsorption/Desorption Coefficient

Not available.

### 12.5. Results of PBT and vPvB assessment

Not Classified as PBT/vPvB by current EU criteria.

### 12.6. Other adverse effects

Not available.

## SECTION 13: DISPOSAL CONSIDERATIONS

#### General information

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority. Do not puncture or incinerate even when empty.

### 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Confirm disposal procedures with environmental engineer and local regulations.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. UN number

UN No. (ADR/RID/ADN)            1950

UN No. (IMDG)                    1950

UN No. (ICAO)                    1950

### 14.2. UN proper shipping name

Proper Shipping Name            AEROSOLS

### 14.3. Transport hazard class(es)

ADR/RID/ADN Class            2.1

ADR/RID/ADN Class            Class 2: Gases

ADR Label No.                    2.1

IMDG Class                        2.1

ICAO Class/Division            2.1

Transport Labels

## TYRE SHINE

14.4. Packing group

ADR/RID/ADN Packing group #

IMDG Packing group #

ICAO Packing group #

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant  
No.

14.6. Special precautions for user

EMS F-D, S-U

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

## SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

## SECTION 16: OTHER INFORMATION

## TYRE SHINE

## Risk Phrases In Full

R12	Extremely flammable.
R22	Harmful if swallowed.
R48/22	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R23	Toxic by inhalation.

## Hazard Statements In Full

H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H280	Contains gas under pressure; may explode if heated.
H222	Extremely flammable aerosol.
H220	Extremely flammable gas.
H330	Fatal if inhaled.
H302	Harmful if swallowed.
H373	May cause damage to organs <<Organs>> through prolonged or repeated exposure.